SAFETY DATA SHEET

Dispenser Aerosol (Citrus Bang)

| SECTION 1: Identification of the substance/mixture and of the company/undertaking | | |
|--|--|--|
| 1.1. Product identifier | | |
| Product name | Dispenser Aerosol (Citrus Bang) | |
| 1.2. Relevant identified uses of the substance or mixture and uses advised against | | |
| Identified uses | Air freshener | |
| 1.3. Details of the supplier of the safety data sheet | | |
| Supplier | C21 Hygiene 628 Harrogate Road Leeds West Yorkshire LS17 8EP (T) 07807 348906 sales@c21hygiene.co.uk | |
| 1.4. Emergency telephone number | | |
| Emergency telephone | 07807 348906 | |
| SECTION 2: Hazards identification | | |

2.1. Classification of the substance or mixture

Classification

Physical hazards

Aerosol 1 - H222, H229

Health hazards Eye Irrit. 2 - H319 Elicitation - EUH208

Environmental hazards

Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC)

F+;R12. R52/53.

Human health

Gas or vapour is harmful on prolonged exposure or in high concentrations. In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

Environmental

The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

Physicochemical

Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

2.2. Label elements

Pictogram



Signal word Hazard statements Danger



Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P102 Keep out of reach of children.

P501 Dispose of contents/container in accordance with local regulations.

P260 Do not breathe vapour/spray.

P271 Use only outdoors or in a well-ventilated area.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| BUTANE | | | 30-60% |
|--|----------------------|---|--------|
| CAS number: 106-97-8 | EC number: 203-448-7 | REACH registration number: Exempt under REACH | |
| Classification Flam. Gas 1 - H220 Press. Gas | | Classification (67/548/EEC or 1999/45/EC) F+;R12 | |
| ISOBUTANE | | | 10-30% |
| CAS number: 75-28-5 | EC number: 200-857-2 | REACH registration number: Exempt under REACH | |
| Classification Flam. Gas 1 - H220 Press. Gas | | Classification (67/548/EEC or 1999/45/EC) F+;R12 | |
| PROPANE | | | 10-30% |
| CAS number: 74-98-6 | EC number: 200-827-9 | REACH registration number: Exempt under REACH | |
| Classification Flam. Gas 1 - H220 Press. Gas | | Classification (67/548/EEC or 1999/45/EC) F+;R12 | |
| PROPAN-2-OL | | | 10-30% |
| CAS number: 67-63-0 | EC number: 200-661-7 | REACH registration number: 01-2119457558-25 | |
| Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336 | | Classification (67/548/EEC or 1999/45/EC) F;R11 Xi;R36 R67 | |

(L) d-para-mentha-1,8-diene

CAS number: 5989-27-5 EC number: 227-813-5 REACH registration number: 01-2119529223-47 M factor (Acute) = 1 M factor (Chronic) = 1

Classification

Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Alpha + Beta Pinenes

CAS number: — EC number: — M factor (Acute) = 100 M factor (Chronic) = 100

Classification

Skin Sens. 1 - H317 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410 Classification (67/548/EEC or 1999/45/EC) N;R50/53. R43.

Classification (67/548/EEC or 1999/45/EC)

Xn;R65. Xi;R38. N;R50/53. R10,R43.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Move affected person to fresh air at once.

Inhalation

If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.

Ingestion

Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact

Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguish with foam, carbon dioxide, dry powder or water fog.

5.2. Special hazards arising from the substance or mixture

Specific hazards

Containers can burst violently or explode when heated, due to excessive pressure build-up. Extremely flammable. Forms explosive mixtures with air. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Containers can burst violently or explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Protective actions during firefighting

<1%

<1%

Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapours. Warn firefighters that aerosols are involved.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate. Avoid inhalation of vapours.

6.2. Environmental precautions

Environmental precautions

Avoid the spillage or runoff entering drains, sewers or watercourses. Contain spillage with sand, earth or other suitable noncombustible material.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb spillage with non-combustible, absorbent material. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of explosion.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Keep away from heat, sparks and open flame. Eliminate all sources of ignition. Do not spray on a naked flame or any incandescent material.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Extremely flammable. Keep away from heat, sparks and open flame. Store at moderate temperatures in dry, well ventilated area. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

7.3. Specific end use(s)

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm Short-term exposure limit (15-minute): WEL 750 ppm

ISOBUTANE

Long-term exposure limit (8-hour TWA): WEL 800 ppm Short-term exposure limit (15-minute): WEL No std.

PROPANE

Long-term exposure limit (8-hour TWA): SUP ppm Short-term exposure limit (15-minute): SUP ppm

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m3 Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m3 WEL = Workplace Exposure Limit

PROPAN-2-OL (CAS: 67-63-0)

| DNEL | Industry - Dermal; Long term systemic effects: 888 mg/kg/day Industry - Inhalation; Long term systemic effects: 500 mg/m3 Consumer - Dermal; Long term systemic effects: 319 mg/kg/day Consumer - Dermal; Long term systemic effects: 26 mg/kg/day Consumer - Inhalation; Long term systemic effects: 89 mg/m3 |
|------|--|
| PNEC | Fresh water; 140.9 mg/l Marine water; 140.9 mg/l Intermittent release; 140.9 mg/l Sediment (Freshwater); 552 mg/kg Sediment (Marinewater); 552 mg/kg STP; 2251 mg/l Soil; 28 mg/kg |

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.

Personal protection

When using do not smoke.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles.

Hand protection

Due to the packaging form, aerosol, risk of skin contact is small. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Hygiene measures

Wash hands after handling. Wash promptly if skin becomes contaminated. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Use appropriate skin cream to prevent drying of skin.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Odour Characteristic.

Flash point <-40 °C°C

Upper/lower flammability or explosive limits

: 1.8

Auto-ignition temperature 410-580°C

Comments

Information given is applicable to the major ingredient.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stability

Avoid the following conditions: Heat, sparks, flames.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid exposing aerosol containers to high temperatures or direct sunlight.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Oxides of carbon. Oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General information

Deliberately concentrating and inhaling the contents of this container is dangerous and can be fatal.

Inhalation

In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Unconsciousness, possibly death.

Skin contact

Skin irritation should not occur when used as recommended. Repeated exposure may cause skin dryness or cracking.

Eye contact

Vapour or spray in the eyes may cause irritation and smarting.

Acute and chronic health hazards

Arrhythmia (deviation from normal heart beat). In high concentrations, vapours and aerosol mists have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Route of entry

Inhalation

Target organs

Central nervous system Respiratory system, lungs

Medical symptoms

Arrhythmia (deviation from normal heart beat). Narcotic effect. Vapours may cause drowsiness and dizziness.

SECTION 12: Ecological Information

Ecotoxicity

No negative effects on the aquatic environment are known. The product is not expected to be toxic to aquatic organisms.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information

Do not puncture or incinerate, even when empty.

Disposal methods

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated because of the risk of an explosion.

| SECTION 14: Transport inform | ation |
|-----------------------------------|--|
| General | This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG. These provisions allow transport of aerosols of less than 1 litre packed in cartons of less than 30kg gross weight to be exempt from control providing that they are labelled in accordance with the requirements of these regulations to show that they are being transported as Limited Quantities. Aerosols not so packed and labelled must show the following. |
| <u>14.1. UN number</u> | |
| UN No. (ADR/RID) | 1950 |
| UN No. (IMDG) | 1950 |
| UN No. (ICAO) | 1950 |
| 14.2. UN proper shipping name | |
| Proper shipping name (ADR/RID) | AEROSOLS |
| Proper shipping name (IMDG) | AEROSOLS |
| Proper shipping name (ICAO) | AEROSOLS |
| Proper shipping name (ADN) | AEROSOLS |
| 14.3. Transport hazard class(es | <u>s)</u> |
| ADR/RID class | 2.1 |
| ADR/RID subsidiary risk | |
| ADR/RID label | 2.1 |
| IMDG class | 2.1 |
| IMDG subsidiary risk | |
| ICAO class/division | 2.1 |
| ICAO subsidiary risk | |
| Transport labels | |
| 14.4. Packing group | |
| Not applicable. | |
| ADR/RID packing group | |
| | |

IMDG packing group

ICAO packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

| 14.6. Special precautions for user | | |
|--|----------|--|
| EmS | F-D, S-U | |
| Emergency Action Code | | |
| Hazard Identification Number (ADR/RID) | | |
| Tunnel restriction code | (D) | |
| 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | | |
| SECTION 15: Regulatory infor | mation | |
| 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture | | |

National regulations

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

EU legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Guidance

Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131. British Aerosol Manufacturers Code of Practice 7th. Edition 1999

| SECTION 16: Other information | |
|-------------------------------|---|
| Revision date | 30/07/2014 |
| Revision | 1 |
| SDS number | 12849 |
| Risk phrases in full | |
| | R10 Flammable. |
| | The product is highly flammable. |
| | R12 Extremely flammable. |
| | Irritating to eyes. |
| | R38 Irritating to skin. |
| | R43 May cause sensitisation by skin contact. |
| | R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| | R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| | R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| | R65 Harmful: may cause lung damage if swallowed. |
| | R67 Vapours may cause drowsiness and dizziness. |
| Hazard statements in full | |

15.2. Chemical safety assessment

EUH208 Contains (L) d-para-mentha-1,8-diene. May produce an allergic reaction.

H222 Extremely flammable aerosol.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H229 Pressurised container: may burst if heated

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.